

DESCRIPTION

PRODUCT COVERED:

[x] USL - Centrifugal Fire Pumps, End Suction

Rated Capacity, US GPM	Size, In.	Model	Pressure Rating, psi	Approx Speed RPM	Maximum Working Pressure Psi	Impeller Diameter, mm.	
300	4x3	EF 80-310	83-148	2950	312	230	310
300	4x3	EF 80-310	86-154	3000	312	230	310
300	4x3	EF 80-310	105-189	3300	312	230	310
300	4x3	EF 80-310	123-220	3550	312	230	310
400	4x3	EF 80-310	78-140	2950	312	230	310
400	4x3	EF 80-310	81-146	3000	312	230	310
400	4x3	EF 80-310	100-180	3300	312	230	310
400	4x3	EF 80-310	118-211	3550	312	230	310
450	4x3	EF 80-310	76-135	2950	312	230	310
450	4x3	EF 80-310	79-141	3000	312	230	310
450	4x3	EF 80-310	98-175	3300	312	230	310
450	4x3	EF 80-310	115-207	3550	312	230	310
500	5x4	EF100-310	89-156	2950	320	230	310
500	5x4	EF100-310	93-161	3000	320	230	310
500	5x4	EF100-310	114-199	3300	320	230	310
500	5x4	EF100-310	134-233	3500	320	230	310
750	6X5	EF 125-310	75-121	2600	257	250	311
750	6X5	EF 125-310	89-143	2800	257	250	311
750	6X5	EF 125-310	97-154	2900	257	250	311
750	6X5	EF 125-310	101-160	2950	257	250	311
750	6X5	EF 125-310	104-166	3000	257	250	311